



Rescue & Fast Rescue Boat Davits of up to 3.5t safe working load

Rescue demands meets optimum quality and reliability

OPTIONS & FEATURES INCLUDE:



Cantilever Outrigger

For fixed offshore installations,
rigs and platforms



A-Frame Pivoting

For sea-going vessels



Single-Arm Slewing

For sea-going vessels

FEATURES:

- SOLAS/LSA certification according EU Wheelmark MED Approval
- Manual, electric &/or hydraulic execution
- Rescue boat &/or life raft application
- IEC rated electrical components
- High speed winch options available
- Options for hazardous area and winterization available
- Tension systems and shock absorbers optional

TYPE	SWL (KN)	CONFIGURATION
Cantilever outrigger	35KN	Rescue boat handling only
Single-arm slewing	14KN	Rescue boat &/or life raft handling
Single-arm slewing	23KN	Rescue boat &/or life raft handling
Single-arm slewing	30KN	Rescue boat &/or life raft handling
Single-arm slewing	23KN	Life raft handling only
Single-arm slewing	30KN	Life raft handling only
Single-arm luffing	35KN	Life raft handling only
A-frame pivoting	35KN	Rescue boat handling only
A-frame hydraulic pivoting	30KN	Rescue boat handling only
A-frame hydraulic pivoting fast rescue	30KN	Fast rescue boat handling only

